

Contact O'Brien for all your tubing requirements.

- Bare Tubing
- PVC Jacketed Tubing – J-Line
- Weatherproof Insulated Tubing – S-Line
- Steam Heated Tubing – TPL / TPH
- Electric Heated Tubing – TPE
- Heated Analyzer Sample Tubing – TRACEPAK® / STACKPAK™

**Specifications**

**Size:** Fractional 1/8" – 1"OD  
Metric 3 – 25mm OD

**Materials:** 316/316L SS  
2.5% Molly 316/316L SS  
Welded 316/316L SS  
Alloy 825  
Duplex / Superduplex  
Copper  
Teflon®  
Other alloys and materials are available as well.

**Construction:** Seamless  
Welded  
20' / 6M Straight Sticks  
Continuous coils up to 2,500F/ 600M

**ID Surface:** Commercial Grade  
Smooth Bore (20Ra / 0.5µm)  
Thermocouple Clean per ASTM A632-S3  
CFOS per CGA G4.1 and ASTM G93  
TrueTube™ EP - Electropolished 316L SMLS SS  
Surface roughness less than 10Ra,  
SEM defect count <40 @ 3500X,  
Cr:Fe ratio > 1.5:1 CrO:FeO ratio > 3:1  
TrueTube™ FS - 316L SMLS SS with SilcoNert® 2000 ID coating  
TrueTube™ EPS - 316L SMLS SS electropolished with additional  
SilcoNert® 2000 ID coating

**Standards:** All tubing conforms to ASTM, EN and DIN international standards.

