

TRACEPAK® Model Number

| Tracepak Model Number X = Alpha # = Numeric | Description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|---|--|---|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|----------|-----------|-----------|------------|----------|-----------|-----------|------------|----------|-----------|-----------|------------|----------|-----------|-----------|-------|----------|-----------|-----------|
| X | Unit of measure – only used for bundle sold and marked in Meters No prefix designates product is sold and marked in feet M = meters | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| / | Separator | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| T | Tracepak Product Designation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| P | This location in the model number will indicate the maximum exposure temperature and duration (continuous or intermittent.) Standard exposure will be assigned a P. Standard exposure is defined as any non-isolated bundle or any bundle with a temperature rating of no more than 400F. Exception to this; bundles with a rating higher than 400F but formaintain only. Any temperature rating other than the exact temperatures shown below will be assigned a Z. Standard exposure P <table border="0" style="width: 100%; margin-top: 10px;"> <tr> <td style="width: 40%;"></td> <td style="width: 20%; text-align: center;">Steam and Continuous</td> <td style="width: 20%; text-align: center;">Intermittent Add 'N' to temperature designation</td> <td style="width: 20%; text-align: center;">One Minute MAX Add 'S' to temperature designation (020730)</td> </tr> <tr> <td>450F/230C</td> <td style="text-align: center;">A</td> <td style="text-align: center;">AN</td> <td style="text-align: center;">AS</td> </tr> <tr> <td>500F/260C</td> <td style="text-align: center;">B</td> <td style="text-align: center;">BN</td> <td style="text-align: center;">BS</td> </tr> <tr> <td>550F/290C</td> <td style="text-align: center;">C</td> <td style="text-align: center;">CN</td> <td style="text-align: center;">CS</td> </tr> <tr> <td>600F/315C</td> <td style="text-align: center;">D</td> <td style="text-align: center;">DN</td> <td style="text-align: center;">DS</td> </tr> <tr> <td>650F/345C</td> <td style="text-align: center;">F</td> <td style="text-align: center;">FN</td> <td style="text-align: center;">FS</td> </tr> <tr> <td>700F/370C</td> <td style="text-align: center;">G</td> <td style="text-align: center;">GN</td> <td style="text-align: center;">GS</td> </tr> <tr> <td>750F/400C</td> <td style="text-align: center;">J</td> <td style="text-align: center;">JN</td> <td style="text-align: center;">JS</td> </tr> <tr> <td>800F/425C</td> <td style="text-align: center;">K</td> <td style="text-align: center;">KN</td> <td style="text-align: center;">KS</td> </tr> <tr> <td>850F/455C</td> <td style="text-align: center;">M</td> <td style="text-align: center;">MN</td> <td style="text-align: center;">MS</td> </tr> <tr> <td>900F/480C</td> <td style="text-align: center;">N</td> <td style="text-align: center;">NN</td> <td style="text-align: center;">NS</td> </tr> <tr> <td>950F/510C</td> <td style="text-align: center;">Q</td> <td style="text-align: center;">QN</td> <td style="text-align: center;">QS</td> </tr> <tr> <td>1000F/540C</td> <td style="text-align: center;">R</td> <td style="text-align: center;">RN</td> <td style="text-align: center;">RS</td> </tr> <tr> <td>1050F/565C</td> <td style="text-align: center;">S</td> <td style="text-align: center;">SN</td> <td style="text-align: center;">SS</td> </tr> <tr> <td>1100F/595C</td> <td style="text-align: center;">T</td> <td style="text-align: center;">TN</td> <td style="text-align: center;">TS</td> </tr> <tr> <td>Other</td> <td style="text-align: center;">Z</td> <td style="text-align: center;">ZN</td> <td style="text-align: center;">ZS</td> </tr> </table> | | Steam and Continuous | Intermittent Add 'N' to temperature designation | One Minute MAX Add 'S' to temperature designation (020730) | 450F/230C | A | AN | AS | 500F/260C | B | BN | BS | 550F/290C | C | CN | CS | 600F/315C | D | DN | DS | 650F/345C | F | FN | FS | 700F/370C | G | GN | GS | 750F/400C | J | JN | JS | 800F/425C | K | KN | KS | 850F/455C | M | MN | MS | 900F/480C | N | NN | NS | 950F/510C | Q | QN | QS | 1000F/540C | R | RN | RS | 1050F/565C | S | SN | SS | 1100F/595C | T | TN | TS | Other | Z | ZN | ZS |
| | Steam and Continuous | Intermittent Add 'N' to temperature designation | One Minute MAX Add 'S' to temperature designation (020730) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 450F/230C | A | AN | AS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 500F/260C | B | BN | BS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 550F/290C | C | CN | CS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 600F/315C | D | DN | DS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 650F/345C | F | FN | FS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 700F/370C | G | GN | GS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 750F/400C | J | JN | JS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 800F/425C | K | KN | KS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 850F/455C | M | MN | MS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 900F/480C | N | NN | NS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 950F/510C | Q | QN | QS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1000F/540C | R | RN | RS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1050F/565C | S | SN | SS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1100F/595C | T | TN | TS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Other | Z | ZN | ZS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Type of bundle/tracer E = electric L = light steam trace H = heavy steam trace | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| # | Number of process tubes 1 = one process tube 2 = two process tubes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X | Jacket Material S = SV47-O'Brien PVC U = TPU | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | Separator | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| XX | Process tube material, construction & wall thickness See Tube List | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ## | Process tube size in 1/8" or mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | Separator | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| XX | Tracer – electric tracer family or steam tube material, construction & wall thickness | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ## | Electric output in w/ft or steam tube size in 1/8" or mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Options Listing (Repeat as necessary) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| / | Separator between each option – repeat as necessary | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X | Jacket Color A = gray (formerly known as "GY" (4/3/03)) R = red B = blue G = green Y = yellow W = white P = purple N = orange U = brown | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X## | Temperature sensor J = J- thermocouple K = K-thermocouple T = T-thermocouple R = 100Ω / 100PT 3 wire RTD XX = distance from power end in units of measure | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| #### | Specials identifier – if "Z" is used in model number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

©2003 O'Brien Corporation • QLT-OBA-TXMOD-A4 • 25 APR 03

ISO 9001:2000



Worldwide Offices:

1900 Crystal Industrial Ct. • St. Louis, MO 63114 • Ph 314/236-2020 • Fax 314/236-2080
 Mallekotstraat 65 • B 2500 Lier Belgium • Ph (+32) 3 491 9875 • Fax (+32) 3 491 9876
 No. 42 Building No. 556 Fa Sai Rd. • Wai Gao Qiao Free Trade-Zone • Shanghai 200131 • Ph 86 21 50482125 • Fax 86 21 50482153
 Suite 400 • 609 14th Street NW • Calgary, AB T2N 2A1 • Ph 403/730-7277 • Fax 403/730-7279
 sales@obcorp.com • www.obrien-analytical.com